



C-STUDIO 5506ACLCF C-STUDIO 6506AC C-STUDIO 7506AC

Datasheet

- Fully customisable A3 multifunctional colour systems for impeccable document output – at a speed of up to 75 ppm in colour and 85 ppm in monochrome.
- Standard Dual Scan Document Feeder for fast and reliable document processing at a speed of up to 240 ipm.
- Advanced media handling combined with superb image quality allows easy in-house creation of a large range of professionally looking documents.

Toshiba's latest series delivers on our promise of Together Information - our commitment to collaborate with clients to provide tailor-made, effective solutions to meet your print, document management, and content needs, while

The new e-STUDIO7506Ac series offers advanced document processing, brilliant colour reproduction and impressive productivity. Equipped with the latest controller technology, e-BRIDGE Next, even complex print jobs are processed sovereign and reliably.

also helping you to meet your green objectives.

State-of-the-art technology must be easy to use. Based on this fundamental idea, Toshiba has designed e-BRIDGE Next to ensure you can interact intuitively with your multifunctional system. The tablet-like user interface not only makes the systems intuitive to use, it can also be customised according to individual preferences.



SPECIFICATIONS

General

Print & Copy Speed	Colour:	55/65/75 ppm (A4) 27/30/37 ppm (A3)
	Monochrome:	65/75/85 ppm (A4) 30/37/40 ppm (A3)
Warm-up Time	Approx. 15 se	econds from low power mode
Paper Size & Weight	Tandem LCF Bypass: 100 >	5R-320 x 460 mm, 60-256 g/m ² ¹⁾ : A4, 60-256 g/m ² x 148 mm-330 x 483 mm, 60-300 g/m ² , · (up to 313.4 x 1,200 mm, 90-163 g/m ²)
Paper Capacity		
Automatic Duplex	A5R-320 x 46	60 mm, 60-256 g/m²
Controller Type	Toshiba e-BF	RIDGE
Control Panel	22.9 cm (9")	Multi-Touch Colour Panel
Memory	Toshiba Secu	Ire HDD 320 GB ²⁾ , 4 GB RAM
Interface		0Base-TX/1000Base-T, JSB 2.0, WLAN ¹⁾ (IEEE802.11b/g/n), Vi-Fi Direct ¹⁾
Dimensions & Weight	955 x 698 x 1	,227 mm (W x D x H), 213 kg
Starter Kit	Drum, develo	per, waste toner box

Сору

Resolution	Scan: 600 x 600 dpi Print: 600 x 600 dpi, 2,400 x 600 dpi with smoothing
First Copy Output Time	Colour: Approx. 6.4/6.4/5.4 seconds Monochrome: Approx. 5.2/4.5/4.1 seconds
Zoom	25-400% (Platen), 25-200% (DSDF)
Copy Modes	Text, Text/Photo, Photo, Printed Image, Map, Image Smoothing
Colour Modes	Auto-Colour (ACS), Full Colour, Twin Colour, Mono Colour, Monochrome
Colour Settings	Hue, Saturation, Colour Balance, RGB adjustment, 5 one-touch modes
Copy Functions	Electronic Sort, Rotate Sort, ID Card Copy, Edge Erase, 2-in-1 / 4-in-1 mode

Fax¹⁾

Communication	Super G3, G3 - (opt. 2nd line), Internet Fax T.37
Transmission Speed	Approx. 3 seconds per page
Compression	JBIG, MMR, MR, MH
Fax Memory	1 GB Transmission/Reception
Network-Fax	Driver for Windows 10/8/7/Vista/Server 2008 (32/64 bit), Server 2012/Server 2008 R2 (64 bit)
Incoming Fax Routing	To shared folders (SMB, FTP, IPX/SPX), E-Mail, e-Filing

System & Security

Device Management	e-BRIDGE Fleet Management System ¹), Top Access for remote administration and configuration
System Features	e-Filing document server for secure storage, Document distribution and Print-on-Demand (1 public box, 200 user boxes), 12,060 one-touch templates for storage of personalised settings or workflows, Scan/Fax Preview, Rip-while-Print, e-BRIDGE Open Platform ¹), Embedded Web Browser, Job Skip
Accounting & Security	Role Based Access, LDAP support, 1,000 depart- ment & 10,000 user codes, Card Reader ¹), Private print, Standard data encryption with Toshiba Secure HDD, Data Overwrite Enabler ¹), IP and MAC address filter, Port filter, Support of SSL and IPsec ¹) protocols, IEEE802.1x support, IEEE2600.1 compliant ¹), Scan to Secure PDF



¹⁾ Optional

 $^{\circ}~~1$ GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed.

Print

Resolution	600 x 600 dpi, 1,200 x 1,200 dpi (2 bit, PostScript driver only), 3,600 x 1,200 dpi with smoothing (PostScript driver only, monochrome)
Page Description Language	PCL5e, PCL5c, PCL6 (PCL XL), XPS and PostScript 3 compatible
Supported Systems	Windows 10/8/7/Vista/Server 2008 (32/64 bit), Windows Server 2012/Server 2008 R2 (64 bit), Mac OS X 10.6.8-10.11, Linux/Unix, Citrix, Novell NetWare (NDPS), SAP, AS/400
Network Protocols	TCP/IP (IPv4/IPv6), IPX/SPX, EtherTalk, NetBios over TCP/IP
Colour Modes	Auto-Colour (ACS), Colour, Twin Colour, Monochrome
Colour Settings	ICC profile colour management, RGB substitution, Brightness, Saturation, Contrast, Colour Balance
Mobile Printing	e-BRIDGE Print & Capture, AirPrint, Mopria Print Service, Google Cloud Print
Print Functions	Universal Printer Driver, Driver Templates, Print from USB, Hold print, Tandem printing

Scan

Resolution	Maximum 600 x 600 dpi
Scan Speed	Dual Scan Document Feeder: up to 240 ipm (300 dpi) in colour and monochrome
Scan Modes	Auto-Colour (ACS), Colour, Greyscale, Monochrome
File Formats	JPEG, Multi/Single Page TIFF/XPS/PDF, Secure PDF, Slim PDF, PDF/A, Searchable PDF ¹⁾ (and other formats like DOCX, XLSX, RTF, TXT) ¹⁾
Scan Functions	WS Scan, Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, Local), Meta Scan ¹), OCR scan ¹), Scan to Box (e-Filing), WIA, TWAIN

OPTIONS

EXTERNAL LARGE CAPACITY FEEDER – MP-2502A

MULTI-STAPLE FINISHER – MJ-1111

SADDLE-STITCH FINISHER – MJ-1112

HOLE PUNCH UNIT – MJ-6106E/ MJ-6106F/ MJ-6106S 2,500-sheets capacity, A4, 60-256 $g/m^{\scriptscriptstyle 2}$

2 trays, 3,250-sheet capacity 50-sheet multi-position stapling A4R-A3, 60-105 g/m² (stapling mode)

2 trays, 3,250-sheet capacity 50-sheet multi-position stapling 5-sheet center folding Saddle-stitched booklets of up to 60 pages A4R-A3, 60-105 g/m² (stapling mode) Available in 2 holes (E), 4 holes (F),

4 holes (S)

SIDE EXIT TRAY – KA-6551-ET FAX BOARD – GD-1370EU WIRELESS LAN / BLUETOOTH MODULE (incl. Wi-Fi Direct) – GN-4020 e-BRIDGE ID-GATE – TWN3/4 HARD DISK DRIVE 320 GB¹¹ (FIPS 140-2 STANDARD) – GE-1230 ACCESSORY TRAY – GR-1250 PANEL TEN-KEY OPTION – GR-1260 DATA OVERWRITE ENABLER – GP-1070 IPsec ENABLER – GP-1080 EMBEDDED OCR ENABLER – GS-1080, GS-1085 MULTI-STATION PRINT ENABLER – GS-1090, GS-1095 HARD COPY SECURITY PRINTING KIT – GP-1190A META SCAN ENABLER – GS-1010 UNICODE FONT ENABLER – GS-1007 ACCESSIBLE ARM – KK-2560

CONFIGURATION



About Toshiba Tec

Toshiba Tec Germany Imaging Systems GmbH is part of the globally operating Toshiba Tec Corporation, active in various high-tech industrial sectors.

Toshiba Tec Corporation is a leading provider of information technology, operating across multiple industries - ranging from retail, education and business services to hospitality and manufacturing. With headquarters in Japan and over 80 subsidiaries worldwide, Toshiba Tec Corporation helps organisations transform the way they create, record, share, manage, and display information.

For more information please contact us:

Toshiba Tec Germany Imaging Systems GmbH

Carl-Schurz-Str. 7 41460 Neuss Germany

Telephone +49 2131-1245-0

Fax +49 2131-1245-402

Website https://www.toshibatec.eu

Together Information is Toshiba's vision for how people and organisations create, record, share, manage and display ideas and data.

It is based on our belief that the most successful organisations are those that communicate information in the most efficient way.

We make that possible through an integrated portfolio of industry specific solutions, all of which reflect Toshiba's commitment to the future of the planet.

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright ©2016 Toshiba Tec. Datasheet_e-STUDIO7506AC_series_GBIDD_201607

Mixed Sources Product group from well-managed for and other controlled sources www.fac.org Cert no. TT-coccossed 91996 Forest Stewardship Council