



Document Manager

- Compact multifunctional A3 colour systems – ideal for up-and-coming businesses
- Excellent colour quality and flexible finishing options which meet your needs
- Individual templates on LCD and in printer driver to allow for efficient and productive workflows
- Environment friendly thanks to improved toner technology

e-STUDIO2050c
e-STUDIO2550c



SAP® Printer Vendor Solution





e-STUDIO2050c
e-STUDIO2550c



General	Print & Copy Speed Colour: 20/25 ppm (A4), 10/12 ppm (A3) B&W: 20/25 ppm (A4), 10/12 ppm (A3) Warm-up Time Approx. 15 seconds from low power mode Paper Size & Weight Cassettes: A5R-A3, 60-163 g/m² Large Capacity Feeder¹⁾: A4, 60-163 g/m² Bypass: 100 x 148 mm-A3, 60-209 g/m² Paper Capacity 250 sheets (Cassettes), 100 sheets (Bypass) Maximum: 2,900 sheets Automatic Duplex A5R-A3, 60-163 g/m² Inner Output Tray 550-sheet capacity Controller Type Toshiba e-BRIDGE Control Panel Tilttable with 9" (22.8 cm) colour LCD touch screen Memory 8 GB SSD, 2 GB RAM, 160 GB Toshiba Secure HDD^{1) 2)} Interface 10/100/1000 BaseT (incl. IPv6), High Speed USB 2.0, WLAN¹⁾ (IEEE802.11b/g) Dimensions & Weight 575 x 590 x 662 mm (W x D x H), ~ 57 kg
Print	Resolution Max. 600 x 600 dpi, 5 bit per colour channel Page Description Languages Max. 600 x 1,200 dpi, 1 bit per colour channel Supported Systems XPS, PCL6 and PostScript 3 compatible Windows 7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Windows Server 2008 R2 (64 bit), Mac OS X, Linux/UNIX, Novell Netware (NDPS), Citrix, SAP, AS/400 Colour Modes Auto-Colour (ACS), Colour, Twin Colour, B&W Colour Settings Brightness, Saturation, Contrast, Colour Balance, ICC profiles management Print Functions Universal Driver, Driver templates, Driver plug-ins, Private/Hold print³⁾, Print from USB, Tandem printing, etc.
Scan	Resolution Max. 600 x 600 dpi Scan Speed Colour & B&W: up to 50 ipm (300 dpi) Scan Modes Auto-Colour (ACS), Colour, Greyscale, B&W File Formats JPEG, Multi/Single Page TIFF/XPS³⁾/PDF, Secure PDF, Slim PDF, Searchable PDF¹⁾ (and other formats like DOC, XLS, RTF, TXT, PDF/A)¹⁾ Scan Functions WS Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local³⁾), Meta Scan¹⁾, Scan to Box (e-Filing³⁾), TWAIN 1.7/1.8/1.9³⁾, Remote TWAIN
Copy	Resolution Scan: 600 x 600 dpi, 10 bit per colour channel First Copy Output Time Print: 600 x 600 dpi, 5 bit per colour channel Colour: Approx. 10.3 seconds B&W: Approx. 8.2 seconds Zoom 25-400% (platen), 25-200% (RADF)¹⁾ Copy Modes Text, Text/Photo, Photo, Printed Image, Map Colour Modes Auto-Colour (ACS), Full Colour, Twin Colour, Mono Colour, B&W Colour Settings Hue, Saturation, Colour Balance, 5 One-touch Modes, RGB Adjustment
Fax¹⁾	Communication Super G3, G3 - (opt. 2nd line), Internet Fax T.37 Transmission Speed Approx. 3 seconds per page Compression JBIG, MMR, MR, MH Fax Memory 100 MB (SSD)/1 GB (HDD)¹⁾ Network-Fax Transmission/Reception Incoming Fax Routing Driver for Windows 7/Vista/XP/Server 2008 R2, etc. To shared folders (SMB, FTP, IPX/SPX), E-mail, e-Filing³⁾
System & Security	Device Management e-BRIDGE Fleet Management System¹⁾, TopAccess System Features for remote administration and configuration e-Filing³⁾ document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 60/12,060³⁾ One-touch Templates for storage of personalised settings or workflows, RIP-while-Print³⁾, e-BRIDGE Open Platform¹⁾, Embedded Web Browser, Job Skip³⁾ Accounting & Security Role Based Access, LDAP support, 50/1,000³⁾ department codes & 100/10,000³⁾ user codes, card reader¹⁾, Quota management, standard data encryption with Toshiba Secure HDD³⁾, Data Overwrite Enabler^{1) 3)}, IP and MAC address filter, port filter, support of SSL and IPsec¹⁾ protocols, IEEE802.1x support, IEEE2600.1 compliant^{1) 3)}, Scan to Secure PDF Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m² if not otherwise mentioned.

OPTIONS

PLATEN COVER – KA-1640PC

RADF – MR-3024

100-sheet capacity, A5R-A3, 35-157 g/m²

JOB SEPARATOR – MJ-5004

2 inner trays, 150- and 250-sheet capacity

INNER FINISHER – MJ-1036

2 trays, 600-sheet capacity
50-sheet multi-position stapling
482 x 508 x 232 mm (W x D x H), ~ 15.3 kg

SADDLE-STITCH FINISHER – MJ-1037

1 tray, 1,000-sheet capacity
50-sheet multi-position stapling
Saddle-stitched booklets of up to 60 pages
500 x 642 x 961 mm (W x D x H), ~ 37 kg

HOLE PUNCH UNIT – MJ-6007/MJ-6008

Options for Finisher MJ-1036/MJ-1037
Available in 2 holes (E), 4 holes (F/S)
126 x 464 x 174 mm (W x D x H), ~ 3.3 kg
120 x 597 x 245 mm (W x D x H), ~ 3.4 kg

CASSETTE – MY-1040

550-sheet capacity, A5R-A3, 60-163 g/m²
575 x 583 x 163 mm (W x D x H), ~ 9.5 kg

PAPER FEED PEDESTAL – KD-1032

550 sheets (1 drawer), A5R-A3, 60-163 g/m²
668 x 701 x 292 mm (W x D x H), ~ 16.3 kg

LARGE CAPACITY FEEDER – KD-1031A4

2,000-sheet capacity, A4, 64-105 g/m²
668 x 735 x 292 mm (W x D x H), ~ 26 kg

OTHER OPTIONS

DESK – MH-2050
PAPER FEED CONTROLLER – GH-1080
DRAWER MODULE – MY-1039
TOSHIBA SECURE HDD 160 GB²⁾ – GE-1220
FAX BOARD – GD-1320EU
FRONT USB KIT – GR-1140
WORK TRAY – KK-4550
DATA OVERWRITE ENabler – GP-1070³⁾
e-BRIDGE ID-GATE – KP-2004/5, TWN3XX
WIRELESS LAN MODULE – GN-1060
META SCAN ENabler – GS-1010
IPsec ENabler – GP-1080
UNICODE FONT ENabler – GS-1007³⁾
e-BRIDGE Re-Rite – GB-1280
DAMP HEATER KIT – MF-2050CE
ACCESSIBILITY ARM – KK-2550

¹⁾ Optional

²⁾ 1GB = 1 billion bytes; the actual formatted capacity is less.
Available capacity will also be less if software applications are pre-installed.

³⁾ Requires Toshiba Secure HDD

TOSHIBA TEC GERMANY IMAGING SYSTEMS GMBH

CARL-SCHURZ-STRASSE 7 · D-41460 NEUSS
TEL. +49(0)2131-12450, FAX +49(0)2131-1245402
WWW.TOSHIBA-EUROPE.COM/TEC

TOSHIBA
Leading Innovation >>>