



Document Manager

- Full multifunctionality including colour scan for increased efficiency
- Total data security with Toshiba's unique secure hard disc protects your documents from unauthorised access
- Latest Toshiba e-BRIDGE technology to ensure reliable quality and ease of use
- Internal toner recycling and low power consumption for maximum eco-efficiency

e-STUDIO256SE
e-STUDIO306SE



SAP® Printer Vendor Solution





e-STUDIO256SE
e-STUDIO306SE



| | |
|-------------------------------------|--|
| <p>General</p> | <p>Print & Copy Speed 25/30 ppm (A4), 16/16 ppm (A3) Approx. 20 seconds</p> <p>Warm-up Time</p> <p>Paper Size & Weight Cassettes: A5R-A3, 64-105 g/m² Large Capacity Feeder¹⁾: A4, 64-105 g/m²</p> <p>Paper Capacity Bypass: A5R-A3, 52-209 g/m² 2 x 550 sheets (Cassettes), 100 sheets (Bypass) Maximum: 3,200 sheets</p> <p>Automatic Duplex</p> <p>Controller Type A5R-A3, 64-105 g/m² Toshiba e-BRIDGE</p> <p>Control Panel 9" (22.8 cm) colour touch panel LCD</p> <p>Memory Toshiba Secure HDD 160 GB²⁾ / 1 GB RAM</p> <p>Interface 10/100/1000BaseT (incl. IPv6), High Speed USB 2.0, WLAN¹⁾ (IEEE802.11b/g), Bluetooth¹⁾</p> <p>Dimensions & Weight 575 x 586 x 756 mm (W x D x H), ~ 59 kg</p> |
| <p>Print</p> | <p>Resolution Max. 2,400 x 600 dpi with smoothing</p> <p>Page Description Languages XPS, PCL6 and PostScript 3 compatible</p> <p>Supported Systems Windows 7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Windows Server 2008 R2 (64 bit), Mac OS X, Linux/UNIX, Novell Netware (NDPS), Citrix, SAP, AS/400</p> <p>Print Functions Universal Driver, Driver templates, Driver plug-ins, Hold print, Print from USB, Tandem printing</p> |
| <p>Scan</p> | <p>Resolution Max. 600 x 600 dpi, 8 bit per colour channel</p> <p>Scan Speed Up to 57/43 (mono/colour) ipm (300 dpi)</p> <p>Scan Modes Auto-Colour (ACS), Colour, Greyscale, B&W</p> <p>File Formats JPEG, Multi/Single Page TIFF/XPS/PDF, Slim PDF, Secure PDF, Searchable PDF¹⁾ (and other formats like DOC, XLS, RTF, TXT, PDF/A)¹⁾</p> <p>Scan Functions Web Services Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local), Meta Scan¹⁾, Scan to Box (e-Filing), TWAIN1.7/1.8/1.9</p> |
| <p>Copy</p> | <p>Resolution Max. 2,400 x 600 dpi with smoothing</p> <p>First Copy Approx. 4.7 seconds</p> <p>Zoom 25-400% (platen), 25-200% (RADF)¹⁾</p> <p>Copy Modes Text, Text/Photo, Photo, Colour Document, Custom</p> |
| <p>Fax¹⁾</p> | <p>Communication Super G3, G3 (opt. 2nd line), Internet Fax T.37</p> <p>Transmission Speed Approx. 3 seconds per page</p> <p>Compression JBIG, MMR, MR, MH</p> <p>Fax Memory 1 GB (HDD) Transmission/Reception</p> <p>Network-Fax Driver for Windows 7/Vista/XP (32/64 bit)</p> <p>Incoming Fax Routing To shared folder (SMB, FTP, IPX/SPX), E-mail, e-Filing</p> |
| <p>System & Security</p> | <p>Device Management e-BRIDGE Fleet Management System¹⁾, TopAccess for remote administration and configuration</p> <p>System Features e-Filing document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, e-BRIDGE Open Platform¹⁾, Embedded Web Browser, Job Skip</p> <p>Accounting & Security Role Based Access, LDAP support, 1,000 department codes & 10,000 user codes, card reader¹⁾, private print, standard data encryption with Toshiba Secure HDD, Data Overwrite Enabler¹⁾, IP and MAC address filter, port filter, support of SSL and IPSec¹⁾ protocols, IEEE802.1x support, IEEE2600.1 compliant¹⁾, Scan to Secure PDF</p> <p>¹⁾ Optional ²⁾ 1GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed.</p> <p>Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m² if not otherwise mentioned.</p> |

OPTIONS

RADF – MR-3021

100-sheet capacity, A5R-A3, 35-157 g/m²

JOB SEPARATOR TRAY – MJ-5004

2 inner trays, 150- and 250-sheet capacity

OFFSET TRAY – MJ-5005

250-sheet capacity

INNER FINISHER – MJ-1032

2 trays, 600-sheet capacity
50-sheet multi-position stapling
482 x 508 x 232 mm (W x D x H), ~ 13 kg

SADDLE-STITCH FINISHER – MJ-1033

1 tray, 1,000-sheet capacity
50-sheet multi-position stapling
Saddle-stitched booklets of up to 60 pages
409 x 624 x 961 mm (W x D x H), ~ 39 kg

HOLE PUNCH UNIT – MJ-6007/MJ-6008

Options for Finisher MJ-1032/MJ-1033
Available in 2-holes (E), 4-holes (F/S)
120 x 245 x 597 mm (W x D x H), ~ 3.3 kg
126 x 463 x 174 mm (W x D x H), ~ 3.4 kg

PAPER FEED PEDESTAL – KD-1025

550-sheet (1 drawer), A5R-A3, 64-105 g/m²
668 x 701 x 291.5 mm (W x D x H), ~ 21 kg

LARGE CAPACITY FEEDER – KD-1026A4

2,000-sheet capacity, A4, 64-105 g/m²
668 x 737 x 292 mm (W x D x H), ~ 26 kg

OTHER OPTIONS

- DESK – MH-2520
- DRAWER MODULE – MY-1033
- FAX BOARD – GD-1250EU-F
- DATA OVERWRITE ENABLER – GP-1070
- e-BRIDGE ID-GATE – KP-2004/5, TWN3XX
- WIRELESS LAN MODULE – GN-1060
- BLUETOOTH MODULE – GN-2020
- META SCAN ENABLER – GS-1010
- IPsec ENABLER – GP-1080
- UNICODE FONT ENABLER – GS-1007
- e-BRIDGE RE-RITE – GB-1280
- ACCESSIBLE ARM – KK-2550

**TOSHIBA TEC GERMANY
IMAGING SYSTEMS GMBH**

CARL-SCHURZ-STRASSE 7 · D-41460 NEUSS
TEL. +49(0)2131-12450, FAX +49(0)2131-1245402
WWW.TOSHIBA-EUROPE.COM/TEC

TOSHIBA
Leading Innovation >>>

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2011 TOSHIBA TEC. DS3065E0BEMD1109