



# Document Manager

- Highly productive monochrome systems for outstanding quality
- Security enhanced systems featuring Toshiba's innovative secure hard disc
- Efficient multifunctionality including high-resolution colour scan
- Sophisticated options for professional document finishing
- Effective power save mode to help save costs and resources

**e-STUDIO556SE**  
**e-STUDIO656SE**  
**e-STUDIO756SE**  
**e-STUDIO856SE**



SAP® Printer Vendor Solution





**e-STUDIO556SE e-STUDIO756SE**  
**e-STUDIO656SE e-STUDIO856SE**



<p><b>General</b></p>	<p><b>Print &amp; Copy Speed</b> 55/65/75/85 ppm (A4), 34/37/40/43 ppm (A3)  <b>Warm-up Time</b> Approx. 130 seconds  <b>Paper Size &amp; Weight</b> Cassettes and Bypass: A5R-A3, 64-209 g/m<sup>2</sup>  Tandem LCF and LCF<sup>1)</sup>: A4, 64-209 g/m<sup>2</sup>  <b>Paper Capacity</b> 2 x 500 sheets (Cassettes), 2,500 sheets A4 (Tandem Large Capacity Feeder), 100 sheets (Bypass)  Maximum: 7,600 sheets  <b>Automatic Duplex</b> A5R-A3, 64-209 g/m<sup>2</sup>  <b>Controller Type</b> Toshiba e-BRIDGE  <b>Control Panel</b> 9" (22.8 cm) colour touch panel LCD  <b>Memory</b> Toshiba Secure HDD 160 GB<sup>2)</sup> / 1 GB RAM  <b>Interface</b> 10/100/1000BaseT (incl. IPv6), High Speed USB 2.0, WLAN<sup>1)</sup> (IEEE802.11b/g), Bluetooth<sup>1)</sup>  <b>Dimensions &amp; Weight</b> 698 x 789 x 1,176 mm (W x D x H), ~ 203 kg</p>
<p><b>Print</b></p>	<p><b>Resolution</b> Max. 2,400 x 600 dpi with smoothing  <b>Page Description Languages</b> XPS, PCL6 and PostScript 3 compatible  <b>Supported Systems</b> Windows 7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Windows Server 2008 R2 (64 bit), Mac OS X, Linux/UNIX, Novell Netware (NDPS), Citrix, SAP, AS/400  <b>Print Functions</b> Universal Driver, Driver templates, Driver plug-ins, Hold print, Print from USB, Tandem printing</p>
<p><b>Scan</b></p>	<p><b>Resolution</b> Max. 600 x 600 dpi, 8 bit per colour channel  <b>Scan Speed</b> Max. 80/77 (mono/colour) ipm (300 dpi)  <b>Document Feeder</b> Max. 100 sheets, A5R-A3, 35-209 g/m<sup>2</sup>  <b>Scan Modes</b> Text, Text/Photo, Photo, Greyscale, Printed  <b>File Formats</b> JPEG, Multi/Single Page TIFF/XPS/PDF, Slim PDF, Secure PDF, Searchable PDF<sup>1)</sup> (and other formats like DOC, XLS, RTF, TXT, PDF/A)<sup>1)</sup>  <b>Scan Functions</b> Web Services Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local), Meta Scan<sup>1)</sup>, Scan to Box (e-Filing), TWAIN1.7/1.8/1.9</p>
<p><b>Copy</b></p>	<p><b>Resolution</b> Max. 2,400 x 600 dpi with smoothing  <b>First Copy</b> Approx. 4/4/3.5/3.5 seconds  <b>Zoom</b> 25-400% (platen), 25-200% (RADF)  <b>Copy Modes</b> Text, Text/Photo, Photo, Custom</p>
<p><b>Fax<sup>1)</sup></b></p>	<p><b>Communication</b> Super G3, G3 (opt. 2<sup>nd</sup> line), Internet Fax T.37  <b>Transmission Speed</b> Approx. 3 seconds per page  <b>Compression</b> JBIG, MMR, MR, MH  <b>Fax Memory</b> 1 GB (HDD) Transmission/Reception  <b>Network-Fax</b> Driver for Windows 7/Vista/XP (32/64 bit)  <b>Incoming Fax Routing</b> To shared folder (SMB, FTP, IPX/SPX), E-mail, e-Filing</p>
<p><b>System &amp; Security</b></p>	<p><b>Device Management</b> e-BRIDGE Fleet Management System<sup>1)</sup>, TopAccess for remote administration and configuration  <b>System Features</b> e-Filing document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, e-BRIDGE Open Platform<sup>1)</sup>, Embedded Web Browser, Job Skip  <b>Accounting &amp; Security</b> Role Based Access, LDAP support, 1,000 department codes &amp; 10,000 user codes, card reader<sup>1)</sup>, private print, standard data encryption with Toshiba Secure HDD, Data Overwrite Enabler<sup>1)</sup>, IP and MAC address filter, port filter, support of SSL and IPsec<sup>1)</sup> protocols, IEEE802.1x support, IEEE2600.1 compliant<sup>1)</sup>, Scan to Secure PDF</p> <p>Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m<sup>2</sup> if not otherwise mentioned.</p>

**OPTIONS**

**MULTI-STAPLE FINISHER – MJ-1027**  
2 trays, 4,000-sheet capacity  
50-sheet multi-position stapling  
616 x 630 x 1,023 mm (W x D x H), ~ 43 kg

**SADDLE-STITCH FINISHER – MJ-1028**  
2 trays, 4,000-sheet capacity  
50-sheet multi-position stapling  
Saddle-stitched booklets of up to 60 pages  
616 x 630 x 1,023 mm (W x D x H), ~ 63 kg

**SADDLE-STITCH FINISHER – MJ-1029**  
2 trays, 4,000-sheet capacity  
100-sheet multi-position stapling  
Saddle-stitched booklets of up to 60 pages  
616 x 630 x 1,023 mm (W x D x H), ~ 66 kg

**HOLE PUNCH UNIT – MJ-6003**  
Option for Finisher MJ-1027/1028/1029  
Available in 2-holes (E), 4-holes (F/S)  
76 x 615 x 275 mm (W x D x H), ~ 5.4 kg

**INSERTER UNIT – MJ-7001**  
Option for Finisher MJ-1027/1028/1029  
1 tray, 100-sheet capacity  
Sheet/Cover Insertion, Manual finishing  
A4-A3, 60-256 g/m<sup>2</sup>  
533 x 604 x 1,072 mm (W x D x H), ~ 20 kg

**LARGE CAPACITY FEEDER – MP-4004A**  
4,000-sheet capacity, A4, 64-209 g/m<sup>2</sup>  
327 x 599 x 617 mm (W x D x H), ~ 37 kg

**OTHER OPTIONS**  
FAX BOARD – GD-1250EU-F  
DATA OVERWRITE ENABLER – GP-1070  
e-BRIDGE ID-GATE – KP-2004/5, TWN3XX  
WIRELESS LAN MODULE – GN-1060  
BLUETOOTH MODULE – GN-2020  
META SCAN ENABLER – GS-1010  
IPsec ENABLER – GP-1080  
UNICODE FONT ENABLER – GS-1007  
e-BRIDGE RE-RITE – GB-1280

<sup>1)</sup> Optional  
<sup>2)</sup> 1GB = 1 billion bytes; the actual formatted capacity is less.  
Available capacity will also be less if software applications are pre-installed.

Technical data is subject to change without prior notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. All rights reserved. We are constantly making efforts to deliver the latest status of data to our partners. Specifications for some models may change in the time between the production and the release of this documentation. Copyright © 2011 TOSHIBA TEC. DS8565EGEBEMD1109